


SAMIFLEX Innenteil Technisches Datenblatt



Ausführung	Bez.	Härte	Farbe	Temperaturbereich
STANDARD	STD	80 Shore A	Blau	-40° C / 80° C
		95 Shore A	Gelb	
HIGH TEMP.	HT	95 Shore A	Orange	-40° C / 140° C
HIGH PERFORMAN.	HD	97 Shore A	Braun	-40° C / 80° C
	HDT	97 Shore A	Rot	-40° C / 140° C

		Torsionssteifigkeit 10 ³ Nm/rad											
Shore Härte	A1	A2	A3	A4	A45	A5	A55	A6	A7	A8	A9	A10	A11
80A	0,2	0,5	1,1	1,9	2,0	2,9	7,5	10,8	19,4	33,5	39,7	74,2	92,7
90A	0,4	1,1	2,0	4,4	5,3	7,3	19	30,9	50,8	95,2	101,9	209	250
96A	1,0	2,1	4,2	9,5	11,2	16	42	65	112	200	214	460	580
97A	1,7	3,8	7,6	17,1	20,2	28,8	79,8	123,5	212,8	380	406	874	1092



SIZE	A00	A0	A1	A2	A3	A4	A45	A5	A55	A6	A7	A8	A9	A10	A11	A12
D (mm).	22	32	40	48	58.5	76	94	106.5	119	127	162	194	233	275	248	390